



**2110 - Stripper Spray
400 ML**

Printing: 07/07/2026

Date of compilation: 03/11/2023

Revised: 07/07/2026

Version: 2 (Replaced 1)

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** 2110 - Stripper Spray
400 ML
- Other means of identification:**
Not relevant
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
Relevant uses (Professional users):
- Solvents and degreasers
For Professional users only.
Uses advised against:
- All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**
Pro Part International
Kozakkenberg 4
5951 DL Belfeld - Netherlands
Phone: +31 (0)77 476 2204
msds@pro-part.eu
www.propart-international.com
- 1.4 Emergency telephone number:** Medical Toxicology Unit, +44 20 7188 7188

SECTION 2: HAZARDS IDENTIFICATION

- The product has been classified in accordance with the information contained in the suppliers' SDS and the additional information from tests carried out by said suppliers
- 2.1 Classification of the substance or mixture:**
GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567):
Classification of this product has been carried out in accordance with GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567).
Aerosol 1: Flammable aerosols, Category 1, H222
Aerosol 1: Pressurised container: May burst if heated., H229
Eye Irrit. 2: Eye irritation, Category 2, H319
- 2.2 Label elements:**
GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567):
Danger
-  
- Hazard statements:**
Aerosol 1: H222 - Extremely flammable aerosol.
Aerosol 1: H229 - Pressurised container: May burst if heated.
Eye Irrit. 2: H319 - Causes serious eye irritation.
- Precautionary statements:**
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211: Do not spray on an open flame or other ignition source.
P251: Do not pierce or burn, even after use.
P280: Wear protective gloves/respiratory protection/eye protection.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.
- 2.3 Other hazards:**
Product does not meet PBT/vPvB criteria
Endocrine-disrupting properties: The product does not meet the criteria.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

- 3.1 Substance:**

2110 - Stripper Spray 400 ML

Printing: 07/07/2026

Date of compilation: 03/11/2023

Revised: 07/07/2026

Version: 2 (Replaced 1)

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

Not relevant

3.2 Mixture:

Chemical description: Solvent/s

Components:

In accordance with Annex II of The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020, the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 115-10-6 EC: 204-065-8 REACH: 01-2119472128-37-XXXX	Dimethyl ether Flam. Gas 1A: H220; Press. Gas: H280 - Danger	  50 - <75%
CAS: 109-87-5 EC: 203-714-2 REACH: 01-2119664781-31-XXXX	Dimethoxymethane Flam. Liq. 2: H225 - Danger	 25 - <50%
CAS: 646-06-0 EC: 211-463-5 REACH: 01-2119490744-29-XXXX	1,3-dioxolane Eye Irrit. 2: H319; Flam. Liq. 2: H225 - Danger	  12.5 - <20%
CAS: Not relevant EC: 926-141-6 REACH: 01-2119456620-43-XXXX	Hydrocarbons, C11-C14,n-alkanes, isoalkanes, cyclics, <2% aromatics Asp. Tox. 1: H304; EUH066 - Danger	 <2.5%
CAS: 108-01-0 EC: 203-542-8 REACH: 01-2119492298-24-XXXX	2-dimethylaminoethanol Acute Tox. 3: H331; Acute Tox. 4: H302+H312; Eye Dam. 1: H318; Flam. Liq. 3: H226; Skin Corr. 1B: H314; STOT SE 3: H335 - Danger	   <0.5%
CAS: 67-56-1 EC: 200-659-6 REACH: 01-2119433307-44-XXXX	methanol Acute Tox. 3: H301+H311+H331; Flam. Liq. 2: H225; STOT SE 1: H370 - Danger	   <0.5%

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Acute toxicity estimate for the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or as determined in accordance with Annex I to that Regulation:

Identification	Acute toxicity		Genus
methanol CAS: 67-56-1 EC: 200-659-6	LD50 oral	100 mg/kg	
	LD50 dermal	300 mg/kg	
	LC50 inhalation mist	0.5 mg/L *	
2-dimethylaminoethanol CAS: 108-01-0 EC: 203-542-8	LD50 oral	1182 mg/kg	
	LD50 dermal	1220 mg/kg	
	LC50 inhalation mist	0.712 mg/L *	

*Equivalent ATE value of the substance applicable to the exposure route of the product. For the ATE value associated with the exposure route of the substance, see section 11.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:



**2110 - Stripper Spray
400 ML**

Printing: 07/07/2026

Date of compilation: 03/11/2023

Revised: 07/07/2026

Version: 2 (Replaced 1)

SECTION 4: FIRST AID MEASURES (continued)

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Not relevant

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

Foam extinguisher (AB), Dry Chemical Powder (ABC) Fire Extinguisher, Carbon dioxide extinguisher (BC)

Unsuitable extinguishing media:

Water jet

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and Self Contained Breathing Apparatus. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...)

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and ground water.

6.3 Methods and material for containment and cleaning up:

It is recommended:



**2110 - Stripper Spray
400 ML**

Printing: 07/07/2026

Date of compilation: 03/11/2023

Revised: 07/07/2026

Version: 2 (Replaced 1)

SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

Prevent the entrance of product in drains, sewers or watercourses. Absorb the spill using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. Collect the product in appropriate containers and manage it according to current legislation.

Spillages in water or sea:

Small spillages:

Contain spillage using barriers or similar equipment. Use suitable absorbents for collection and treat the waste in accordance with current regulations.

Large spillages:

If possible, contain spillage in open water using barriers or similar equipment. If this is not possible, try to control its spread and collect the product with suitable mechanical means. Always consult experts before using dispersants and make sure you have the necessary approvals if they are to be used. Treat the waste according to current regulations.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Specific storage requirements

Minimum Temp.: 5 °C

Maximum Temp.: 20 °C

Maximum time: 6 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be assessed in the workplace:

EH40/2005 Workplace exposure limits, fourth edition, published 2020:

Identification	Occupational exposure limits		
Dimethyl ether CAS: 115-10-6	WEL (8h)	400 ppm	766 mg/m ³
	WEL (15 min)	500 ppm	958 mg/m ³
Dimethoxymethane CAS: 109-87-5	WEL (8h)	1000 ppm	3160 mg/m ³
	WEL (15 min)	1250 ppm	3950 mg/m ³
2-dimethylaminoethanol CAS: 108-01-0	WEL (8h)	2 ppm	7.4 mg/m ³
	WEL (15 min)	6 ppm	22 mg/m ³
methanol ⁽¹⁾ CAS: 67-56-1	WEL (8h)	200 ppm	266 mg/m ³
	WEL (15 min)	250 ppm	333 mg/m ³

- CONTINUED ON NEXT PAGE -

**2110 - Stripper Spray
400 ML**

Printing: 07/07/2026

Date of compilation: 03/11/2023

Revised: 07/07/2026

Version: 2 (Replaced 1)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

⁽¹⁾ Skin

DNEL (Workers):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Dimethyl ether CAS: 115-10-6 EC: 204-065-8	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
	Inhalation	Not relevant	Not relevant	1894 mg/m ³	Not relevant
Dimethoxymethane CAS: 109-87-5 EC: 203-714-2	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	17.9 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	126.6 mg/m ³	Not relevant
1,3-dioxolane CAS: 646-06-0 EC: 211-463-5	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	1.18 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	3.306 mg/m ³	Not relevant
2-dimethylaminoethanol CAS: 108-01-0 EC: 203-542-8	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	1.2 mg/kg	Not relevant	0.25 mg/kg	Not relevant
	Inhalation	5.28 mg/m ³	13.53 mg/m ³	1.76 mg/m ³	1.76 mg/m ³
methanol CAS: 67-56-1 EC: 200-659-6	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	20 mg/kg	Not relevant	20 mg/kg	Not relevant
	Inhalation	130 mg/m ³	130 mg/m ³	130 mg/m ³	130 mg/m ³

DNEL (General population):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Dimethyl ether CAS: 115-10-6 EC: 204-065-8	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
	Inhalation	Not relevant	Not relevant	471 mg/m ³	Not relevant
Dimethoxymethane CAS: 109-87-5 EC: 203-714-2	Oral	Not relevant	Not relevant	18.1 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	18.1 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	31.5 mg/m ³	Not relevant
2-dimethylaminoethanol CAS: 108-01-0 EC: 203-542-8	Oral	Not relevant	Not relevant	0.126 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
	Inhalation	Not relevant	Not relevant	0.438 mg/m ³	Not relevant
methanol CAS: 67-56-1 EC: 200-659-6	Oral	4 mg/kg	Not relevant	4 mg/kg	Not relevant
	Dermal	4 mg/kg	Not relevant	4 mg/kg	Not relevant
	Inhalation	26 mg/m ³	26 mg/m ³	26 mg/m ³	26 mg/m ³

PNEC:

Identification					
Dimethyl ether CAS: 115-10-6 EC: 204-065-8	STP	160 mg/L	Fresh water	0.155 mg/L	
	Soil	0.045 mg/kg	Marine water	0.016 mg/L	
	Intermittent	1.549 mg/L	Sediment (Fresh water)	0.681 mg/kg	
	Oral	Not relevant	Sediment (Marine water)	0.069 mg/kg	
Dimethoxymethane CAS: 109-87-5 EC: 203-714-2	STP	10000 mg/L	Fresh water	14.577 mg/L	
	Soil	4.654 mg/kg	Marine water	1.477 mg/L	
	Intermittent	Not relevant	Sediment (Fresh water)	13.135 mg/kg	
	Oral	Not relevant	Sediment (Marine water)	Not relevant	
1,3-dioxolane CAS: 646-06-0 EC: 211-463-5	STP	1 mg/L	Fresh water	19.7 mg/L	
	Soil	2.62 mg/kg	Marine water	1.97 mg/L	
	Intermittent	0.95 mg/L	Sediment (Fresh water)	77.7 mg/kg	
	Oral	Not relevant	Sediment (Marine water)	7.77 mg/kg	
2-dimethylaminoethanol CAS: 108-01-0 EC: 203-542-8	STP	10 mg/L	Fresh water	0.066 mg/L	
	Soil	0.01 mg/kg	Marine water	0.004 mg/L	
	Intermittent	0.661 mg/L	Sediment (Fresh water)	0.246 mg/kg	
	Oral	Not relevant	Sediment (Marine water)	0.015 mg/kg	

- CONTINUED ON NEXT PAGE -

**2110 - Stripper Spray
400 ML**

Printing: 07/07/2026

Date of compilation: 03/11/2023

Revised: 07/07/2026

Version: 2 (Replaced 1)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification				
methanol	STP	100 mg/L	Fresh water	20.8 mg/L
CAS: 67-56-1	Soil	100 mg/kg	Marine water	2.08 mg/L
EC: 200-659-6	Intermittent	1540 mg/L	Sediment (Fresh water)	77 mg/kg
	Oral	Not relevant	Sediment (Marine water)	7.7 mg/kg

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<UKCA marking>> or <<CE marking>>. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Remarks
 Mandatory respiratory tract protection	Filter mask for gases, vapours and particles (Filter type: A2B2P3)	Replace when an increase in resistance to breathing is observed and/or a smell or taste of the contaminant is detected.

C.- Specific protection for the hands

Pictogram	PPE	Remarks
 Mandatory hand protection	Chemical protective gloves (Material: Butyl, Breakthrough time: > 480 min, Thickness: 0.4 mm)	Replace the gloves at any sign of deterioration.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

Pictogram	PPE	Remarks
 Mandatory face protection	Panoramic glasses against splash/projections.	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Not relevant

F.- Additional emergency measures

It is advised to implement additional emergency equipments in workplaces that are particularly exposed to the product or in situations where risk assessments highlight the necessity of such equipments.

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls:

To comply with environmental protection regulations, it is recommended to prevent any spillage of the product and its container. For more detailed information, please refer to subsection 7.1.D.

The Volatile Organic Compounds in Paints, Varnishes and Vehicle Refinishing Products Regulations 2012:

V.O.C. (Supply):	100 % weight
V.O.C. density at 20 °C:	800 kg/m ³ (800 g/L)



**2110 - Stripper Spray
400 ML**

Printing: 07/07/2026

Date of compilation: 03/11/2023

Revised: 07/07/2026

Version: 2 (Replaced 1)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:	Aerosol
Appearance:	Not relevant *
Colour:	☐ White
Odour:	Sweet
Odour threshold:	Not relevant *

Volatility:

Boiling point at atmospheric pressure:	Not relevant *
Vapour pressure at 20 °C:	400000 Pa
Vapour pressure at 50 °C:	Not relevant *
Evaporation rate at 20 °C:	Not relevant *

Product description:

Density at 20 °C:	800 kg/m ³
Relative density at 20 °C:	Not relevant *
Dynamic viscosity at 20 °C:	Not relevant *
Kinematic viscosity at 20 °C:	Not relevant *
Kinematic viscosity at 40 °C:	Not relevant *
Concentration:	Not relevant *
pH:	Not relevant *
Relative vapour density at 20 °C:	Not relevant *
Partition coefficient n-octanol/water 20 °C:	Not relevant *
Solubility in water at 20 °C:	Not relevant *
Solubility properties:	Not relevant *
Decomposition temperature:	Not relevant *
Melting point/freezing point:	Not relevant *
Recipient pressure:	Not relevant *

Flammability:

Flash Point:	Not relevant *
Flammability (solid, gas):	Not relevant *
Autoignition temperature:	235 °C (Propellant)
Lower flammability limit:	2.5 % Volume
Upper flammability limit:	26.2 % Volume

Particle characteristics:

Median equivalent diameter:	Not relevant *
-----------------------------	----------------

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties:	Not relevant *
Oxidising properties:	Not relevant *
Corrosive to metals:	Not relevant *
Heat of combustion:	Not relevant *
Aerosols-total percentage (by mass) of flammable components:	Not relevant *

Other safety characteristics:

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



**2110 - Stripper Spray
400 ML**

Printing: 07/07/2026

Date of compilation: 03/11/2023

Revised: 07/07/2026

Version: 2 (Replaced 1)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Surface tension at 20 °C: Not relevant *

Refraction index: Not relevant *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Precaution	Precaution	Risk of combustion	Avoid direct impact	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

Contains glycols. It is recommended not to breathe the vapours for prolonged periods of time due to the possibility of effects that are hazardous to the health.

The product has been classified in accordance with the information contained in the suppliers' SDS and the additional information from tests carried out by said suppliers

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for skin contact. For more information see section 3.
- Contact with the eyes: Causes serious eye irritation.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

**2110 - Stripper Spray
400 ML**

Printing: 07/07/2026

Date of compilation: 03/11/2023

Revised: 07/07/2026

Version: 2 (Replaced 1)

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
- IARC: Not relevant
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous as a result of a single exposure. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Not relevant

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
Dimethyl ether CAS: 115-10-6 EC: 204-065-8	LD50 oral	>2000 mg/kg	
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation gases	164000 ppm (4 h)	Rat
Dimethoxymethane CAS: 109-87-5 EC: 203-714-2	LD50 oral	6423 mg/kg	Rat
	LD50 dermal	>5000 mg/kg	Rabbit
	LC50 inhalation vapour	>20 mg/L	
1,3-dioxolane CAS: 646-06-0 EC: 211-463-5	LD50 oral	>2000 mg/kg	
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation vapour	68.4 mg/L (4 h)	Rat
Hydrocarbons, C11-C14,n-alkanes, isoalkanes, cyclics, <2% aromatics CAS: Not relevant EC: 926-141-6	LD50 oral	>2000 mg/kg	
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation vapour	>20 mg/L	
methanol CAS: 67-56-1 EC: 200-659-6	LD50 oral	100 mg/kg	
	LD50 dermal	300 mg/kg	
	LC50 inhalation vapour	3 mg/L	
2-dimethylaminoethanol CAS: 108-01-0 EC: 203-542-8	LD50 oral	1182 mg/kg	Rat
	LD50 dermal	1220 mg/kg	Rabbit
	LC50 inhalation vapour	5.97 mg/L	Rat

Acute Toxicity Estimate (ATE mix):

ATE mix		Ingredient(s) of unknown toxicity
Oral	25000 mg/kg (Calculation method)	0 %
Dermal	75000 mg/kg (Calculation method)	0 %
LC50 inhalation mist	66.57 mg/L (4 h) (Calculation method)	0 %



**2110 - Stripper Spray
400 ML**

Printing: 07/07/2026

Date of compilation: 03/11/2023

Revised: 07/07/2026

Version: 2 (Replaced 1)

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Only the physical form mist can occur during any reasonably expected use of the product, including when the product is used to produce a new product.

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product does not meet the criteria.

SECTION 12: ECOLOGICAL INFORMATION

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

The product has been classified in accordance with the information contained in the suppliers' SDS and the additional information from tests carried out by said suppliers

12.1 Toxicity:

Acute toxicity:

Identification	Concentration	Species	Genus
Dimethoxymethane CAS: 109-87-5	LC50	6990 mg/L (96 h)	Pimephales promelas
	EC50	Not relevant	
	EC50	Not relevant	
1,3-dioxolane CAS: 646-06-0	LC50	Not relevant	
	EC50	772 mg/L (48 h)	Daphnia magna
	EC50	877 mg/L (72 h)	Pseudokirchneriella subcapitata
2-dimethylaminoethanol CAS: 108-01-0	LC50	146 mg/L (96 h)	Leuciscus idus
	EC50	98.4 mg/L (48 h)	Daphnia magna
	EC50	35 mg/L (72 h)	Scenedesmus subspicatus
methanol CAS: 67-56-1	LC50	15400 mg/L (96 h)	Lepomis macrochirus
	EC50	Not relevant	
	EC50	Not relevant	

12.2 Persistence and degradability:

Substance-specific information:

Identification	Degradability	Biodegradability	
1,3-dioxolane CAS: 646-06-0 EC: 211-463-5	BOD5	Not relevant	Concentration
	COD	Not relevant	Period
	BOD5/COD	Not relevant	% Biodegradable
Hydrocarbons, C11-C14,n-alkanes, isoalkanes, cyclics, <2% aromatics CAS: Not relevant EC: 926-141-6	BOD5	Not relevant	Concentration
	COD	Not relevant	Period
	BOD5/COD	Not relevant	% Biodegradable
2-dimethylaminoethanol CAS: 108-01-0 EC: 203-542-8	BOD5	Not relevant	Concentration
	COD	Not relevant	Period
	BOD5/COD	Not relevant	% Biodegradable
methanol CAS: 67-56-1 EC: 200-659-6	BOD5	1236 g O2/g	Concentration
	COD	Not relevant	Period
	BOD5/COD	Not relevant	% Biodegradable

12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Bioaccumulation potential	
1,3-dioxolane CAS: 646-06-0 EC: 211-463-5	BCF	3
	Pow Log	-0.37
	Potential	Low
2-dimethylaminoethanol CAS: 108-01-0 EC: 203-542-8	BCF	3
	Pow Log	-0.73
	Potential	Low

- CONTINUED ON NEXT PAGE -



**2110 - Stripper Spray
400 ML**

Printing: 07/07/2026

Date of compilation: 03/11/2023

Revised: 07/07/2026

Version: 2 (Replaced 1)

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Bioaccumulation potential	
methanol	BCF	
CAS: 67-56-1	Pow Log	-0.77
EC: 200-659-6	Potential	

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
Dimethyl ether CAS: 115-10-6	Koc	Not relevant	Henry	Not relevant
	Conclusion	Not relevant	Dry soil	Not relevant
	Surface tension	1.136E-2 N/m (25 °C)	Moist soil	Not relevant
Dimethoxymethane CAS: 109-87-5	Koc	Not relevant	Henry	Not relevant
	Conclusion	Not relevant	Dry soil	Not relevant
	Surface tension	2.12E-2 N/m (25 °C)	Moist soil	Not relevant
1,3-dioxolane CAS: 646-06-0	Koc	3.46	Henry	Not relevant
	Conclusion	Very High	Dry soil	Not relevant
	Surface tension	7.17E-2 N/m (20 °C)	Moist soil	Not relevant
2-dimethylaminoethanol CAS: 108-01-0	Koc	1.2	Henry	1.8E-4 Pa·m ³ /mol
	Conclusion	Very High	Dry soil	Not relevant
	Surface tension	3.111E-2 N/m (25 °C)	Moist soil	Not relevant
methanol CAS: 67-56-1	Koc	Not relevant	Henry	4.61E-1 Pa·m ³ /mol
	Conclusion	Not relevant	Dry soil	Yes
	Surface tension	2.355E-2 N/m (25 °C)	Moist soil	Yes

12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product does not meet the criteria.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class
16 05 04*	gases in pressure containers (including halons) containing hazardous substances	Hazardous

Type of waste:

HP3 Flammable

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance The Waste (England & Wales) Regulations 2011, 2011 No. 988. As under 15 01 of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of UK REACH the provisions related to waste management are stated:

UK legislation: The Waste (England & Wales) Regulations 2011.

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2025 and RID 2025:

**2110 - Stripper Spray
400 ML**

Printing: 07/07/2026

Date of compilation: 03/11/2023

Revised: 07/07/2026

Version: 2 (Replaced 1)

SECTION 14: TRANSPORT INFORMATION (continued)



- 14.1 UN number:** UN1950
14.2 UN proper shipping name: AEROSOLS
14.3 Transport hazard class(es): 2
Labels: 2.1
14.4 Packing group: N/A
14.5 Environmental hazards: No
14.6 Special precautions for user
Tunnel restriction code: D
Physico-Chemical properties: see section 9
Limited quantities: 1 L
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code: Not relevant

Transport of dangerous goods by sea:

With regard to IMDG 42-24:



- 14.1 UN number:** UN1950
14.2 UN proper shipping name: AEROSOLS
14.3 Transport hazard class(es): 2
Labels: 2.1
14.4 Packing group: N/A
14.5 Marine pollutant: No
14.6 Special precautions for user
Special regulations: 63, 959, 190, 277, 327, 344
EmS Codes: F-D, S-U
Physico-Chemical properties: see section 9
Limited quantities: 1 L
Segregation group: Not relevant
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code: Not relevant

Transport of dangerous goods by air:

With regard to IATA/ICAO 2026:



- 14.1 UN number:** UN1950
14.2 UN proper shipping name: AEROSOLS, flammable
14.3 Transport hazard class(es): 2
Labels: 2.1
14.4 Packing group: N/A
14.5 Environmental hazards: No
14.6 Special precautions for user
Physico-Chemical properties: see section 9
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code: Not relevant

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

- Prior Informed Consent (PIC) List: Not relevant
- Substances listed in UK candidate list of substances of very high concern (SVHCs): Not relevant
- Substances listed in UK REACH Authorisation List (Annex 14): Not relevant

The Control of Major Accident Hazards Regulations 2015:

Section	Description	Lower-tier requirements	Upper-tier requirements
P3a	FLAMMABLE AEROSOLS	150.000	500.000

- CONTINUED ON NEXT PAGE -



**2110 - Stripper Spray
400 ML**

Printing: 07/07/2026

Date of compilation: 03/11/2023

Revised: 07/07/2026

Version: 2 (Replaced 1)

SECTION 15: REGULATORY INFORMATION (continued)

Restrictions to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII UK REACH, etc):

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

1. Shall not be placed on the market in articles, after 6 August 2026, if, under the test conditions specified in Appendix 14, the concentration of formaldehyde released from those articles exceeds:

- (a) 0,062 mg/m³ for furniture and wood-based articles
- (b) 0,080 mg/m³ for articles other than furniture and wood-based articles.

The first subparagraph shall not apply to:

- (a) articles in which formaldehyde or formaldehyde releasing substances are exclusively naturally present in the materials from which the articles are produced
- (b) articles that are exclusively for outdoor use under foreseeable conditions
- (c) articles in constructions, that are exclusively used outside the building shell and vapour barrier and that do not emit formaldehyde into indoor air
- (d) articles exclusively for industrial or professional use unless formaldehyde released from them leads to exposure of the general public under foreseeable conditions of use
- (e) articles for which the restriction laid down in entry 72 applies
- (f) articles that are biocidal products within the scope of Regulation (EU) No 528/2012 of the European Parliament and of the Council¹
- (g) devices within the scope of Regulation (EU) 2017/745
- (h) personal protective equipment within the scope of Regulation (EU) 2016/425
- (i) articles intended to come into contact directly or indirectly with food within the scope of Regulation (EC) No 1935/2004
- (j) second-hand articles.

2. Shall not be placed on the market in road vehicles after 6 August 2027 if, under the test conditions specified in Appendix 14, the concentration of formaldehyde in the interior of those vehicles exceeds 0,062 mg/m³.

The first subparagraph shall not apply to:

- (a) road vehicles exclusively for industrial or professional use unless the concentration of formaldehyde in the interior of those vehicles leads to exposure of the general public under foreseeable conditions of use
- (b) second-hand vehicles.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.

The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2020.

Control of Substances Hazardous to Health Regulations 2002 (as amended)

EH40/2005 Workplace exposure limits.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.

Texts of the legislative phrases mentioned in section 2:

H319: Causes serious eye irritation.

H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567):



**2110 - Stripper Spray
400 ML**

Printing: 07/07/2026

Date of compilation: 03/11/2023

Revised: 07/07/2026

Version: 2 (Replaced 1)

SECTION 16: OTHER INFORMATION (continued)

Acute Tox. 3: H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled.

Acute Tox. 3: H331 - Toxic if inhaled.

Acute Tox. 4: H302+H312 - Harmful if swallowed or in contact with skin.

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.

Eye Dam. 1: H318 - Causes serious eye damage.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Flam. Gas 1A: H220 - Extremely flammable gas.

Flam. Liq. 2: H225 - Highly flammable liquid and vapour.

Flam. Liq. 3: H226 - Flammable liquid and vapour.

Press. Gas: H280 - Contains gas under pressure, may explode if heated.

Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.

STOT SE 1: H370 - Causes damage to organs.

STOT SE 3: H335 - May cause respiratory irritation.

Classification procedure:

Eye Irrit. 2: Calculation method

Aerosol 1: Calculation method

Aerosol 1: Calculation method

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://echa.europa.eu>

<http://eur-lex.europa.eu>

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

LC50: Lethal Concentration 50

EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient

Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at UK, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -